

Complete catalogue

Always perfectly prepared – with the LEHNER innovations in the areas of agricultural technology, winter technology, and special-purpose machines.



SPREADING AND DOSING AT 12 V

LEHNER Maschinenbau

LEHNER Maschinenbau GmbH emerged from LEHNER Agrar GmbH, which was founded in 1956 by Josef Lehner. LEHNER is led today by the second generation, Helmut Lehner, whose vision and wealth of innovative ideas has made LEHNER Maschinenbau GmbH what it is in many areas today – the market leader for 12V spreading technology throughout Europe.

LEHNER is the synonym for innovative quality products which are used principally in agriculture, viticulture, and fruit growing, as well as winter road maintenance. Since the very beginning, LEHNER has concentrated on development and strictly supervised final assembly of its products, whose components are all manufactured in Germany to our specifications and fulfil the highest quality requirements. This way, only products with the distinction “Made in Germany” leave our company. This is just one of the reasons why the innovations from LEHNER enjoy such demand worldwide, and the export share of the spreading technology today is an impressive 37% – with the trend continuing upwards.



TABLE OF CONTENTS:



You can obtain LEHNER products not only from our numerous **trading partners in Germany and Austria**, but also worldwide. Online at www.lehner.eu, you will find a corresponding overview of our **country representations** and the LEHNER partner in your vicinity.

VENTO®	4–5
VENTO® Duo	6
SuperVario®	7
LIMAX®	8
AgroDos®	9
MiniVario®	10
VINERO®	11
POLARO®	12
POLARO® E	13
POLARO® L/XL	14
ÖITiger®	15
TUBARO®	16
TendoMat®	17
SpeltEx®, SpeltEx® Pro	18
Dispensing guns	19
AUTO-DOSIS	20
Brackets	21–22
Accessories	23–27

Drive

12 V

Fan

1-100%
stepless

Spreading width

<12 m>
maximum

Outlets

8 | 16
hoses

Control panel



VENTO II




AGRICULTURAL MACHINERY

VENTO®

Our pneumatic hose spreader with high-powered 12 V fan for reliably spreading grass, catch and cover crops, fertilisers, slug pellets, and other granular products.

The VENTO® also masters high sowing rates (e.g. 40 kg/ha grass or 120 kg/ha seed) without problem. All functions can be controlled directly on the control panel and changed while on the move.



The VENTO®
in action



Further information: www.lehner.eu

The VENTO® impresses in every respect:

- Working width 1 to 6 or 12 m
- 12 V high-powered fan (1 or 2)
- Hopper (120, 230, 360 or 500 l) with residue emptying flap
- Control panel with 3.3 inch graphic display as standard
- Speed-dependent dosing and headland management system as standard
- Agitator and empty indicator in the hopper
- Supplied as standard with:
 - 8 or 16 baffle plates with U-brackets for mounting
 - 1 or 2 rotary feeder shafts (2x 5.0ml blue/outlet) and star feeder set
 - LEHNER Superflex hose (25 m or 50 m)
 - 1 or 2 calibration bags, and scales for calibration tests
 - Battery cable 6 mm² (6 m); control cable (6 m)
 - Transport and mounting frame



Tool-free installation and removal of the rotary feeder and the hoses



8 or 16 baffle plates including installation material and blue feeder shaft and rotary feeder set as standard



VENTO II control panel:

- Machine start/stop
- Speed-dependent dispensing via 7-pin signalling socket
- Manual operation is possible at any time (blower speed and rotary feeder rpm)
- Headland management system via 7-pin signal socket
- Automatic residue emptying
- Automatic calibration
- 18 languages available
- Program memory for up to 75 calibration tests

Drive

12 V

Spreading width



Fan

1-100%
stepless

Hopper

Split in
two

50/50 | 65/35

Control panel



VENTO II



AGRICULTURAL MACHINERY

Further information: www.lehner.eu

VENTO® Duo

Pneumatic hose spreader with two-chamber system for simultaneously spreading large legumes and small seed crops; features include:

- Infinitely adjustable working width from 1 to 6 m
- 2x 12 V high-powered fan and separately controlled rotary feeder shafts
- Both hopper sizes are available with a 50/50 or 65/35 split



VENTO II
control panel:

- Machine start/stop
- Speed-dependent dispensing via 7-pin signalling socket
- Manual operation is possible at any time (blower speed and rotary feeder rpm)
- Headland management system via 7-pin signal socket
- Automatic residue emptying
- Automatic calibration
- 18 languages available
- Program memory for up to 75 calibration tests



VENTO® Duo
230 l

VENTO® Duo
500 l

Drive

12 V

Spreading width

2–24 m

Examination
according to
JKI RiLi
3-1.0

Warning

Signal

Control panel

LAS 4



AGRICULTURAL MACHINERY

Further information: www.lehner.eu

SuperVario®

The 12 Volt all-round spreader (300 W) for spreading grasses, catch and cover crops, slug pellets, and other granulates; features include:

- Infinitely adjustable working width from 2 to 24 m
- Agitator finger as standard, especially for sowing grass seed
- 10 times autostart for agglomerated spreading material
- Infinitely adjustable distributor blades for adjusting the spreading pattern



LAS 4 control panel as standard:

- Machine start/stop
- Adjustment of the spreading disc speed to set the working width
- Infinite adjustment of the spreading dosage
- Visual/acoustic warning when the hopper level reaches the minimum (empty indicator) or the valve is not in position
- Voltage testing, etc.

OPTIONAL

AUTO-DOSIS

Speed-dependent dispensing (see page 20)

Drive

12V

Spreading width

3–30 m

Examination

according to
JKI RiLi
3-1.0

Warning

Signal

Control panel

LAS 4



AGRICULTURAL MACHINERY

Further information: www.lehner.eu

LIMAX[®]

The 12 Volt slug pellet spreader (300 W) with infinitely adjustable working width from 3 to max. 30 m and outstandingly even spreading pattern; features include:

- Best sideways spreading for slug pellets of all single disc spreaders tested (IRSTEVA test institute)
- Spreading disc with two long distributor blades offering a total of 90 setting options and strike point adjustment (+/-20°) for spreading pattern optimisation



LAS 4 control panel as standard:

- Machine start/stop
- Adjustment of the spreading disc speed to set the working width
- Infinite adjustment of the spreading dosage
- Visual/acoustic warning when the hopper level reaches the minimum (empty indicator) or the valve is not in position
- Voltage testing, etc.

Drive

12 V

Reversing



Approved

by:



Examination according to JKI RiLi 3-1.0

Control panel



AGRICULTURAL MACHINERY

Further information: www.lehner.eu

AgroDos[®]

The 12 V granulate spreader with the safest technology on the market for spreading a great variety of granular materials during potato cultivation; features include:

- Manual or route-dependent operation possible
- On stopping, the rotary feeder valve rotates backwards by 25°. This completely prevents any "trickling".
- Application rate adjustment +/- 20%
- Incl. 2x fishtail distributors



Test number: G1956



LAS 4 PSM control panel included in scope of delivery:

- Machine start/stop
- Adjust the speed of the star feeder lock to determine the discharge rate (infinitely adjustable)
- Speed-dependent dispensing via 7-pin signal socket (tractor) as standard
- Automatic residue emptying
- Electrical calibration and setting up of your own products
- Setting the EHR signal
- Program memory for up to 12 calibration tests
- 5 languages available, etc.

Drive

12 V

Spreading width

0.8–6 m

Warning

Signal

Control panel

LAS 4

Metal parts

stainless steel (1.4301)



AGRICULTURAL MACHINERY

Further information: www.lehner.eu

MiniVario®

12 Volt spreader for grasses, catch and cover crops, fertilisers, and other granulates, for use especially in viticulture, fruit, asparagus, or hop growing; features include:

- Infinitely adjustable working width 0.8 to 6 m (up to 12 m optionally)
- Water-resistant gear motors and cables
- Movable spreading disc for one-sided spreading
- VA special agitator



LAS 4 control panel as standard:

- Machine start/stop
- Adjustment of the spreading disc speed to set the working width
- Infinite adjustment of the spreading dosage
- Visual/acoustic warning when the hopper level reaches the minimum (empty indicator) or the valve is not in position
- Voltage testing, etc.

OPTIONAL

AUTO-DOSIS

Speed-dependent dispensing (see page 20)

Drive

12 V

Spreading width



0.8–2.2 m

Spreading rate

Up to max.
400 kg
per hectare

Warning



Signal

Control panel



LAS 4

Metal parts

stainless steel
(1.4301)



Wide area output



Spreading in the rows

AGRICULTURAL MACHINERY

Further information: www.lehner.eu

VINERO®

The 12 V combination spreader for viticulture, fruit growing, hops, and horticulture, surface and row spreading of grasses, catch and cover crops, and fertilisers; features include:

- Working width from 0.8 to 2.2 m
- 10 times autostart for agglomerated spreading material
- Bladed agitator with separate 12 V drive
- 4 or 8 hose outlets



LAS 4 control panel as standard:

- Machine start/stop
- Infinite adjustment of the spreading dosage, based on the rotational speed and valve position settings
- Visual and acoustic warning when the hopper level reaches the minimum (empty indicator) or the valve is not in position
- Voltage testing, etc.

Standard rail not included in standard scope of delivery.



Drive

12 V

Spreading width

0.8–6 m

Agitator

Grit up to 8 mm

Metal parts

stainless steel (1.4301)

Verkabelung



Control panel



Manual dosing:

On the POLARO®, the flow rate is set manually on the machine, using the dosing valve; it is infinitely adjustable.

SNOW MACHINERY

Further information: www.lehner.eu

POLARO®

The spreader attachment for installation on all vehicles with a 12 Volt supply – for the targeted and even spreading of salt, grit, sand, and even fertilizer; features include:

- Infinitely adjustable working width from 0.8 to 6 m (up to 12 m optionally)
- 10 times autostart for agglomerated spreading material
- Frame, valve, and spreading disc made from non-rusting stainless steel as standard



LAS control panel as standard:

- Machine start/stop
- Slide valve Open/Closed
- Infinitely adjustable spreading disc speed to set the working width



VA agitator made of stainless steel with patented LEHNER agitator system

Drive

12 V

Spreading width

0.8–6 m

Agitator

Grit up to 8 mm


Metal parts

stainless steel (1.4301)

Cables



Control panel



Electronic dosing:

With the POLARO® E, the discharge rate is set and adjusted conveniently at the control panel, directly from the driver's seat.

SNOW MACHINERY

Further information: www.lehner.eu

POLARO® E

The universal spreader attachment for installation on all vehicles with a 12 Volt supply, for spreading of salt, grit, sand, and even fertiliser; features include:

- Infinitely adjustable working width from 0.8 to 6 m (up to 12 m optionally)
- Frame, valve, spreading disc, and VA agitator with patented agitator system made from non-rusting stainless steel
- One-sided spreading possible



LAS 4 control panel as standard:

- Machine start/stop
- Adjustment of the spreading disc speed to set the working width
- Infinite adjustment of the spreading dosage
- Visual/acoustic warning when the hopper level reaches the minimum (empty indicator) or the valve is not in position
- Voltage testing, etc.

OPTIONAL

AUTO-DOSIS

Speed-dependent dispensing (see page 20)

Drive

12 V

Spreading width



0.8–6 m

Screw conveyor

Grit up to 6 mm

Metal parts

stainless steel (1.4301)

IP rating

IP67

Capacity

1,000 kg max.

OPTIONAL

AUTO-DOSIS



SNOW MACHINERY

Further information: www.lehner.eu

POLARO® L/XL

The powerful 12 V spreaders for efficiently dispensing salt, grit, and sand over a large area – for professional winter road maintenance without a special vehicle; features incl.:

- Infinitely adjustable working width from 0.8 to 6 m (up to 12 m optionally)
- Polyurethane hopper with screw conveyor and vibrator with automatic start-up, for a constant material flow
- Hopper extension for increased capacity (accessory)



POLARO® L
380 l hopper



POLARO® XL
550 l hopper



Control panel provided as standard:

- Machine start/stop
- Adjustment of the spreading disc speed to set the working width
- Altering the screw speed to control the discharge rate and boost function for briefly discharging larger quantities of spreading material
- Three memory keys (P1 to P3) for individual settings
- Empty warning, residue emptying, and service prompts
- Automatic breakaway for screw conveyor, etc.

Drive

12V

Spreading width



0.5–2 m

Control panel



LAS



SPECIAL-PURPOSE MACHINES

Further information: www.lehner.eu

ÖITiger[®]

12 V spreader for the precise, efficient and safe dispensing of oil-binding agents from fire brigade or local authority vehicles; features include:

- Infinitely adjustable working width from 0.5 to 2 m
- Valve and spreading disc made from non-rusting stainless steel
- OPTIONAL: Saline agitator in the hopper for very slow-flowing oil binding agents
- For front or rear installation



LAS control panel as standard:

- Machine start/stop
- Slide valve Open/Closed
- Infinitely adjustable spreading disc speed to set the working width

Drive

12 V

Spreading width



0.8-1.4 m

Spreading rate

Up to max.
45 kg
per minute

Warning



Signal

Control panel



LAS 4

Agitator

Grit up
to 6 mm



SPECIAL-PURPOSE MACHINES

Further information: www.lehner.eu

TUBARO®

The 12 V hose spreader for smaller rollers in road construction, for even distribution and precise dosing of sand or grit without forming tracks; features include:

- Working width from 0.8 to 1.4 m
- Valve and agitator made from non-rusting stainless steel
- Water-resistant gear motors and cables
- Saline agitator for slow-flowing material as standard



LAS 4 control panel included in scope of delivery:

- Machine start/stop
- Infinite adjustment of the spreading dosage, based on the rotational speed and valve position settings
- Visual and acoustic warning when the hopper level reaches the minimum (empty indicator) or the valve is not in position
- Voltage testing, etc.

Drive

12 V

Capacity

2.5 mm wire
about 2 km
per reel

Effectiveness

Fence
2 ha in
20 min

Metal parts

stainless steel
(1.4301)

Control panel



Reel

2x 
as standard



SPECIAL-PURPOSE MACHINES

Further information: www.lehner.eu


TendoMat®

Fence winder for quickly and effortlessly winding wire in and out during fencing work around cornfields or pastures; features include:

- 12 V electric motor for unwinding (bottom reel) and winding (top reel) the wire
- Slip clutch for overload protection
- The scope of delivery includes two Ø 350 mm stainless steel reels

2 hectares in only 20 minutes:

With the TendoMat®, even large areas of farmland can be fenced in record time – without muscle power.



TendoMat® control panel as standard:

- Machine start/stop
- Selection of winding speed: fast/slow

Connection



Dehulling

Up to approx.
500 g
per min.

Filling hopper

Approx.
4 liter
capacity

Power

Total
1.5 kW



The innovative
dehuller for
small volumes:
unique in
Europe!

SPECIAL-PURPOSE MACHINES

Further information: www.lehner.eu

SpeltEx[®]

Sample dehuller with aspiration for fast and professional dehulling of raw spelt kernels for quality inspections in goods acceptance testing.

- Simple, user-friendly operation
- Precise display of all dehulling setting parameters for reproducible results (approx. 500 g/Min.)
- Robust technology and easy to clean




SpeltEx[®]

SpeltEx[®] Pro



Control unit of the SpeltEx[®] with On/Off, Emergency Stop and ammeter.



Control unit of the SpeltEx[®] Pro: as for the SpeltEx[®], but with stepless fine adjustment of dosage quantity  based on the speed of the rotary feeder shaft.



Easy to handle

By pushing the dispensing gun, the bait is placed in the mouse burrow. When the dispensing gun is lifted, the outlet is closed again. The quantity of bait can be adjusted mechanically.

SPECIAL-PURPOSE MACHINES

Further information: www.lehner.eu

Dispensing guns

Application aid for manual, targeted laying of granular rodenticides directly in mouse burrows; reduces the risk of back injury.

Instead of having to bend down, the user can operate the dispensing gun while standing comfortably, and the bait can be dispensed directly into the mouseholes.




Backpack dispensing gun:

- 5 litre hopper
- Adjustable carrying strap and hose
- Height-adjustable handle

Dispensing gun:

- Length: 1,050 mm
- Tare weight: 250 g
- Capacity: 500 ml
- Tube diameter: Ø 26 mm



- Overall length: 850 to 1,250 mm
- Hose length: approx. 1,000 mm
- Tare weight: 1.5 kg
- Capacity: 5,000 ml
- Tube diameter: Ø 26 mm

AUTO-DOSIS: Speed-dependent dispensing



AUTO-DOSIS automatically adjusts the valve position in line with the travel speed.

After you have selected the material and entered the desired spreading width and discharge rate per hectare or per m², AUTO-DOSIS automatically reacts to braking and acceleration manoeuvres, and controls the dosing valve accordingly. The set discharge rate thus remains constant at all times.

AUTO-DOSIS and headland management system via 7-pin signal socket

Here, the travel speed is recorded via the 7-pin signal socket on the tractor. In this version, the signal socket also provides the headland management system. This way, EHR pulses cause the spreader valve to close or open when the hydraulics are raised or lowered.

AUTO-DOSIS via GPS receiver

The speed is determined by GPS and transmitted to the control panel.



Headland management system

With this additional device, the valve of the spreader is automatically closed/opened when the hydraulics are raised/lowered, and the valve setting is displayed on the control panel.

Automatic valve control via sensor signal:

For tractors without a 7-pin signal socket, a magnet with sensor is attached to the top or bottom link of the hydraulics. The sensor senses the lifting or lowering motion and sends the spreader a signal to open or close the valve.




LEHNER BRACKETS



LEHNER BRACKETS



Drawbar coupling holder,
foldable



Drawbar coupling holder, lowerable



Spare wheel bracket



ATV/quad holder „Heck“



Bracket for lawn mower tractor

You can find further
brackets and detailed
information online at:
www.lehner.eu

LEHNER ACCESSORIES



LEHNER ACCESSORIES



VENTO® ISOBUS cable (3.5 m)




25 m LEHNER Superflex hose with baffle plate/bracket



VENTO® blind plugs



Battery cable incl. bracket, cable length 5 m




Guide plate is adjustable



Adjustable deflector plate for "ploughing on the right"

LEHNER ACCESSORIES



LEHNER ACCESSORIES



LED work light with cable, 3 m (open end)



LED lighting set, magnetic



“Crystal” LED rotating beacon light



Spreading disc motor for larger working widths up to 12 m



Various lashing straps



Spray guard 90 cm high with double hollow seam/meter

LEHNER ACCESSORIES



Reversing camera, 7" LCD colour display, digital wireless IP69K



Three-point linkage for POLARO® L (CAT I und II)



Connection cable M12 (2, 5 o. 10 m) for POLARO® L/XL



Spelt valve incl. fastening material for SpeltEx® and SpeltEx® Pro



Cooler for retrofitting for the SpeltEx®

You can find further accessories and detailed information online at:
www.lehner.eu

Please visit us on:



Facebook



YouTube

Subject to technical modifications © LEHNER Maschinenbau GmbH 07/2021



LEHNER Maschinenbau GmbH / Häuslesäcker 14 / D-89198 Westerstetten, Germany
Tel.: +49 (0)7348 9596-22 / Fax: +49 (0)7348 9596-40 / e-mail: info@lehner.eu / www.lehner.eu