



Drive

**12V**

Capacity

2.5 mm wire  
**about 2 km**  
per reel

Effectiveness

Fence in  
**2 ha in**  
**20 min**

Metal parts

**Stainless steel**

Control panel



Reel

**2x**   
as standard



SPECIAL-PURPOSE MACHINES

# TendoMat®

Electric fence winder with 12 V drive for quickly and effortlessly erecting and dismantling wire fences around cornfields or pastures.

# WIND AND UNWIND FENCING WIRE WITHOUT THE USUAL EFFORT – TendoMat®

With the TendoMat®, painstaking, time-consuming, and tiring winding and unwinding of fencing wire is now a thing of the past. Fitted quickly and easily to a tractor, all-terrain vehicle, car trailer or quad bike, even large areas of farmland can be fenced in record time (2 ha in just 20 min) – without muscle power. In addition, wires up to 1 km long (depending on wire diameter) can be pulled directly out of the fence posts and wound back up.

Equipment features of the TendoMat® from LEHNER:

- 12 V electric motor for unwinding (bottom reel) and winding (top reel) the wire
- Metal parts of stainless steel
- Slip clutch for overload protection
- Battery and control cable included in delivery
- Control panel for switching on/off and selecting a fast/slow winding speed



You can find further brackets, holders and accessories at [www.lehner.eu](http://www.lehner.eu)


## TendoMat®

### TECHNICAL DATA



|                         |                            |
|-------------------------|----------------------------|
| Dimensions without reel | 770x380x900 mm             |
| Weight                  | 25 kg                      |
| Motor power             | 100W                       |
| Fuse                    | 25 A                       |
| Winding speed           | approx. 80 – 130 m/min     |
| Speed range             | 70 – 136 rpm               |
| Power consumption       | Normal operation up to 18A |
| Operating temperature   | -10 to +50 °C              |
| Storage temperature     | -30 to +50 °C              |
| Battery cable           | 5 m (2.5 mm <sup>2</sup> ) |
| Control cable           | 6 m                        |

### ACCESSORIES



**Replacement reel**  
Ø 350 mm (2x as standard).



**Holding device for tailboard**  
for attaching to a vertical wall.



**Spare wheel bracket** for  
attaching the TendoMat® to an  
all-terrain vehicle.



**Three-Point-Frame CAT 0, CAT I, CAT II** for attaching to the top and bottom links of the hydraulics.



**LEHNER®**  
Streuen & Dosieren mit 12 Volt