



LEHNER®

Streuen & Dosieren mit 12 Volt

Drive

12V

Spreading width

<42 m>
maximum

Spreading discs

4 – 8
individually
controllable

Fan

0-100%
stepless

Hoses

8
maximum

Spreading rate

25 kg/ha
at 6.5 km/h

Control panel



VENTO II



120 l

230 l

360 l

500 l

AGRICULTURAL MACHINERY

VENTO® Pro

Individually designed pneumatic hose spreader with two high-powered fans and 4 – 8 spreading discs for dispensing slug pellets or cover crops over a width of max. 42 metres – ideal for field sprayers.

VENTO® Pro: FOR MOUNTING FREELY ON AN EXISTING SPRAYER BOOM

In the VENTO® Pro, two 12 V high-powered fans convey the spreading material through hose and pipe connections to individually controllable spreading discs (between 4 and 8), which can dispense cover crops or slug pellets over a width of up to 42 m. As the VENTO® Pro is individually designed to suit the carrier vehicle or type of use, please address your request for a quote directly to LEHNER.

Equipment features of the VENTO® Pro from LEHNER:

- 8 hose outlets for connecting 4–8 spreading discs, in line with the individual design
- Metal hopper with a capacity of 120 l or 230 l (360 l and 550 l available on request)
- 12 V high-powered fans (2x) and control panel
- Speed-dependent dosing and headland management system via 7-pin signal socket included as standard
- Device control according to JKI RiLi 3-1.0 incl. report + seal
- Depending on the design, the product package includes:
 - LEHNER Superflex hose (50 m)
 - Spreading discs with holder, rotary feeder shaft, rotary feeder set, blind plugs and fastening materials
 - Battery cable approx. 6 m, VENTO® control cable (20 m) and connecting cable to the disconnection box (20 m)
 - Transport and mounting frame, which the customer may need to adapt for installation

INCLUSIVE
Test seal and
test report



With VENTO II control panel as standard

For further information visit: www.lehner.eu

VENTO® Pro TECHNICAL DATA



Hopper capacity (litres)	120 l	230 l
Dimensions (LxWxH) in mm	969x527x1,009	997x570x1,199
Weight	61 kg	84 kg
No of fans / spreading width	2x / up to 42 m	
Speed spreading discs	200 – 1,500 rpm	
Spreading rate	10 kg at 15 km/h or 25 kg at 6.5 km/h	
Total power consumption	max. 45 A	
Motor power consumption	10 A	
Operating/storage temperature	-10 to +50 °C	



Spreading discs with holder

The spreading disc can be individually, infinitely adjusted via the control panel and feature two distributor blades. To ensure the lowest possible power consumption, they are automatically started one after the other. Each spreading disc can have a working width of up to 12 m, depending on the spreading material.



LEHNER®
Streuen & Dosieren mit 12 Volt